



PHOTOVOLTAIC GLASS		1850 x 1200
		6" Poly Crystalline
Electrical data test conditions (STC)		
Nominal peak power	233	P _{mpp} (Wp)
Open-circuit voltage	36,66	V _{oc} (V)
Short-circuit current	8,04	I _{sc} (A)
Voltage at nominal power	30,84	V _{mpp} (V)
Current at nominal power	7,56	I _{mpp} (A)
Power tolerance not to exceed	±10	%
STC: 1000 w/m ² , AM 1.5 and a cell temperature of 25°C, stabilized module state.		
Mechanical description		
Length	1850	mm
Width	1200	mm
Thickness	9,8	mm
Surface area	2,22	sqm
Weight	44,40	Kgs
Cell type	6" Poly	Crystalline
No PV cells / Transparency degree	60	38%
Front Glass	4 mm	Tempered Glass Low-Iron
Rear Glass	4 mm	Tempered Glass
Thickness encapsulation	1,80 mm	EVA Foils
Category / Color code		
Junction Box		
Protection	IP65	
Wiring Section	2,5 mm ² or 4,0 mm ²	
Limits		
Maximum system voltage	1000	V _{sys} (V)
Operating module temperature	-40...+85	°C
Temperature Coefficients		
Temperature Coefficient of P _{mpp}	-0,451	%/°C
Temperature Coefficient of V _{oc}	-0,361	%/°C
Temperature Coefficient of I _{sc}	+0,08	%/°C

*All technical specifications are subject to change without notice by Onyx Solar

